

The PT Cloud Control Column allows for different check-in & check-out options at the Points of Entry and Exit (PoE) – QR Code Ticket, Parking Card, RFID, Mobile Phone (QR Code or/and Bluetooth), ALPR and DSRC.

Unattended payment at the exit as an option (Pay@Exit).

The 10.4" high brightness color, touch display with state-of-the art energy-saving LED backlight, provides excellent information displaying and communication capabilities.

## Features

Innovative and ergonomic design  
10.4" color display with touch and protective glass  
Illuminated ticket button  
Temperature monitoring and control

**QR Code Scanner** with high visibility LED aimer: laser-free aiming provides an accurate scan indication, creating a customer friendly operating environment while removing the risk of eye injury.

Mobile Phone Reading: easily scans bar codes directly from mobile device, almost as if they were printed on paper.

Excellent performance on decoding poor or damaged bar codes. Outstanding near-field barcode reading and omnidirectional reading.  
Advanced motion tolerance optics. Integrated good-read beeper.

## Options

Ram Protectors  
Cloud based VoIP intercom  
ADA compliant SIP Intercom



**Ticket Printer** with Industry leading print speed of up to 220mm/s and higher reliability at an MCBF of 60 Million Lines.

Large Paper Roll supporting up to a 254 mm | 10" paper roll for many hours of unattended operation.

Innovative looping presenter prevents paper jams by printing the receipt in full before providing it to the user.

## PARKING TELECOM CONTROL COLUMN

TECHNICAL SPECIFICATION

ELECTRICAL	
Supply Voltage	100 to 240 V AC
Frequency	50 - 60Hz
DISPLAY	
LCD Technology	Active matrix TFT LCD
Diagonal Size	10.4"
Active Display Area	210.2 mm (H) x 158.4 mm (V)
Brightness	Sunlight readable, high brightness (2,000 nits). Auto adjustable by Light Sensor
Native Resolution	800 x 600
Aspect Ratio	4:3
Viewing Angle (typical)	130° (H), 110° (V)
QR CODE SCANNER	
Scan Pattern	Area Image (838 x 640 pixel array)
Motion Tolerance	>270 cm/s (106 in/s) at focal point
Scan Angle	Horizontal: 42.4°, Vertical: 33°
Reading Indicators	Beeper, Good Read LED
Reading Ranges	10 mil: 4.7 cm to 21.6 cm   1.9 in to 8.5 in
RFID READER	
Operating Frequency	Dual 125 kHz and 13.56 MHz
Typical Maximum Read Range	2.5 - 7.6 cm   1.0" - 3.0" dependent upon proximity card type and environment
Indicators	Tri-state LED, dual tone beeper
Power Supply	USB Self-powered; PoE
Interface	USB, Serial RS-232, Ethernet
TICKET PRINTER	
Paper Width	Adjustable, from 45 mm to 82.5 mm   1.77 in to 3.25 in
Paper Thickness	0.06 mm to 0.15 mm
Paper Diameter	max 254 mm   10 in
Print Method	Direct Thermal
Print Speed	Up to 220 mm/sec   8.66 in/sec
Ticket Presenter	Loop presenter
Bezel	Flashing LED Bezel
Sensors	Near End Paper Sensor
MCBF	60 million lines
Cutter	1 million cuts
Presenter	1 million receipts
ENVIORNMENTAL	
Ambient Temperature	-20°C to +50°C   -4F to +122F
Storage Temperature	-20°C to +60°C   -4F to +140F
Relative Humidity	max. 95% non-condensing
Protection Class Column Housing	IP54
Housing design	Powder coated aluminum and stainless steel
Compliant with	CE, UL
Color	Signal White RAL 9006 and Black Anthracite RAL 7021
DIMENSIONS	
Dimensions (W x D x H)	360 mm x 450 mm x 1380 mm   14.1 in x 17.7 in x 54.3 in

\* Performance may be impacted by bar code quality and environmental conditions

For more information: [parkingtelecom.com/en/](http://parkingtelecom.com/en/)

**Parking Telecom EMEA**

74 Voie Magellan, PA Alpespace, 73800 Ste Helene du Lac, France



Parking Telecom reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Parking Telecom, the Parking Telecom logo are either trademarks or registered trademarks of IngeniQue Corp. All other trademarks are the property of their respective owners. © 2018 Parking Telecom EMEA SAS. All rights reserved.

