

The PT Unattended Point of Sale (uPOS) is an easy and flexible unattended parking payment solution.

QR code, RFID, License Plate Number based payments. Provides EMV chip and, Contactless (including NFC) card acceptance 24/7.

State-of-the art energy-saving 10.4" LED touch screen display with backlight, which uses less electricity to operate. Designed for "touch" with proven quality and reliability.



Features

Innovative and ergonomic design
10.4" color, touch display

QR Code Scanner with high visibility LED aimer: Laser-free aiming provides an accurate scan indication, creating a customer friendly operating environment while removing the risk of eye injury.

Mobile Phone Reading: Easily scans bar codes directly from mobile device, almost as if they were printed on paper.

Excellent performance on decoding poor or damaged bar codes. Outstanding near-field barcode reading and omnidirectional reading.

Advanced motion tolerance optics. Integrated good-read beeper.

No mechanical components
Zero maintenance
Wall or pole mounted

Options

Receipt Printer
PT post for mounting
ADA compliant SIP Intercom
Cloud based VoIP intercom

PARKING TELECOM CASHLESS uPOS

TECHNICAL SPECIFICATION

ELECTRICAL	
Supply Voltage	100 to 240 V AC
Frequency	50-60Hz
DISPLAY	
LCD Technology	Active matrix TFT LCD
Diagonal Size	10.4"
Brightness	High brightness (1200 nits).
Native Resolution	800 x 600
BARCODE SCANNER	
Scan Pattern	Area Image (838 x 640 pixel array)
Motion Tolerance	>270 cm/s (106 in/s) at focal point
Scan Angle	Horizontal: 42.4°, Vertical: 33°
Reading Indicators	Beeper, Good Read LED
Reading Ranges	10 mil: 4.7 cm to 21.6 cm 1.9 in to 8.5 in
RFID READER	
Operating Frequency	Dual 125 kHz and 13.56 MHz
Typical Maximum Read Range	2.5 - 7.6 cm 1.0" - 3.0" dependent upon proximity card type and environment
Indicators	Tri-state LED, dual tone beeper
Power Supply	USB Self-powered; PoE
Interface	USB, Serial RS-232, Ethernet
ENVIROMENTAL	
Ambient Temperature	-20°C to +50°C -4F to +122F
Storage Temperature	-20°C to +60°C -4F to +140F
Relative Humidity	max. 95% non-condensing
Protection Class Column Housing	IP54
Housing design	Industrial polyester housing
Color	White
DIMENSIONS	
Dimensions (W x D x H)	615 mm x 415 mm x 230 mm 24.21 in x 16.34 in x 6.69 in

* Performance may be impacted by bar code quality and environmental conditions

For more information: parkingtelecom.com/en/

Parking Telecom EMEA

74 Voie Magellan, PA Alpespace, 73800 Ste Helene du Lac, France

Parking Telecom reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Parking Telecom, the Parking Telecom logo are either trademarks or registered trademarks of IngeniQue Corp. All other trademarks are the property of their respective owners. © 2018 Parking Telecom EMEA SAS. All rights reserved.

